



FAST AG SOLUTIONS **SPRAYERS**



FAST DESIGNED
BY FARMERS | FOR FARMERS

FAST DESIGNED BY FARMERS | FOR FARMERS

Founded in 1990 by Verlyn Fast, a farmer seeking to increase the productivity of his own operations, FAST's mission is to provide quality products at competitive prices, backed by dependable service. Today, FAST represents farmers and engineers coming together to produce high quality sprayer and liquid fertilizer equipment that is both practical and productive. Our welders, fabricators, assemblers, and painters are skilled craftsmen who take pride in their work.

We realize how important it is for today's farmers to continue to become more efficient and profitable, so our equipment is designed and built to make your job quick, accurate, and safe. Your investment in FAST equipment will pay dividends for years to come.

Our goal at FAST is to make you a life-long customer, one piece of equipment at a time.

100% EMPLOYEE OWNED

In 2015, FAST became a 100% employee-owned company through a merger with WASP, Inc. (now known as FAST Global Solutions, Inc.), based out of Glenwood, MN. This partnership has allowed both companies to diversify and continue to grow by devoting more resources to new product design and innovation as well as having more workforce and capacity available to meet customer demands. Together, both FAST AG and FAST Global are committed to continuing to provide quality, dependable products while also pushing the envelope on new technologies to help increase the bottom line of your farming operation.

QUALITY DESIGN

Over the years FAST has continued to invest in equipment to increase the automation and consistency of our manufacturing process to provide high quality machinery for farmers. Our manufacturing facility currently utilizes flat laser tables, a tube laser, a robotic welding cell, multiple press brakes, and an automated powder coat paint system.



FAST VS. SELF-PROPELLED

MORE CAPACITY, LESS COMPACTION

Today's Ag environment is changing, operating margins are tighter, and pre-emerge spraying is becoming increasingly important. All of which make pull-type and 3-point mounted sprayers a better fit for your operation.


Annual Total Sprayer Cost per Acre Farmed: \$6.23 vs. \$12.15 — \$59,200 over five years!

- 2,000 acre farmer (three passes per year)
- New 120' FAST 9518T – Ultraglide, AutoYaw - \$77,750
- Used 120' Self Propelled 1000 gallon tank - \$225,000
- 50% Depreciation after five years for both
- Tractor is already available
- Tractor Cost of Operation/Depreciation - \$0.78 per acre
- Self-Propelled Fuel - \$0.30 per acre
- Hidden Costs – Additional Drive Train Maintenance

FAST SPRAYERS OFFER A SOLUTION THAT WILL HELP YOU **REDUCE YOUR COSTS** PER ACRE, **BECOME MORE PRODUCTIVE** WITH LARGER TANK CAPACITY, AND **INCREASE YOUR APPLICATION WINDOW** SINCE A TRAILER SPRAYER CAN OPERATE MORE EFFECTIVELY IN WET CONDITIONS.

**CAN YOU
AFFORD
TO LAY OUT AN
ADDITIONAL
\$59,200 OVER
THE NEXT
FIVE YEARS?**





FAST HYDRAULIC AUTOYAW SYSTEM TAKE THE STRESS OUT OF YOUR BOOM

FAST offers a Hydraulic AutoYaw cushioning system that is controlled through an ISO compatible display (2630/Pro 700, etc.).

This system has sensors that are mounted to the center section and senses at all times what the position of each wing is. If the wing starts moving forward or rearward due to a sudden start, stop, turn, etc., the sensor will detect that and apply hydraulic cushioning through the fold cylinder to bring the boom to a controlled/cushioned stop and also to bring the boom back to its "home" position.

This system helps significantly when there is sudden tractor movements caused by auto-steer, sudden stops, when turning on ends, and also help prevent any "boom walk" that may be experienced with other booms.

This is a very unique system that is offered by FAST and provides benefits that no other trailer or 3-point sprayer can match. The FAST ISO Hydraulic AutoYaw System is standard on all 9500T and 973PT sprayers (120' and 132' booms).

FAST TRACKS

TIRED OF SEEING RUTS IN YOUR FIELDS?

Significant Ground Pressure Reduction

Our 15" CAMSO track system significantly reduces your footprint in the field by offering a 78% reduction in ground pressure compared to 380/90R46 Single Tires. If you compare a 2400 gallon 120' FAST sprayer on tracks to a common 120' self-propelled sprayer with a 1200 gallon tank, the FAST sprayer provides 2.7 times more flotation while also carrying twice as many gallons!

Smooth Ride/Hillside Benefits

The larger surface area provided by tracks also gives a more smooth trailer ride and helps the trailer hold much better on hillsides to reduce crop damage.

Industry Leading Durability/Flexibility

Track System designs have come a long way in recent years to increase durability. The tracks offered by FAST feature a cast undercarriage for added strength, oil bath bearings for reduced maintenance, as well as (4) fore-aft pivot points and (5) independent axle side-to-side pivot points per track. This added flexibility helps ensure that the entire track surface stays in contact with the ground over varying field and roading conditions to reduce heat build-up and provide increased durability.

Larger Application Window

The reduced footprint offered by tracks allow you to spray in a wider variety of field conditions without as much risk of getting stuck or making significant "ruts" in your field. This is extremely important with today's resilient weeds that require more passes through the field, pre-emerge spraying becoming a necessity, and spraying 20+ gallons per acre also becoming very common.



STEERABLE HITCH

FAST offers a Steerable Hitch option that will automatically compensate to stay in your tractor tracks when turning on headlands and while on hillsides. This system ties into your ISO display and through the use of rotary sensors and accelerometers automatically monitors the hitch position and detects trailer movements to know when to compensate. The Steerable Hitch will automatically center and lock itself when you back into corners along with re-engaging when you start moving forward again. This helps significantly reduce the crop damage on your headlands and on hillsides, keeping more bushels in your field, and will leave your fields looking much more consistent.



FAST DESIGNED BY FARMERS | FOR FARMERS

Operators have tested FAST sprayers over hundreds of thousands of acres and we continue to hear the same feedback as operators love the FAST boom ride and short-coupled design. Our equipment is “Designed by Farmers, For Farmers”, and we demonstrate this by focusing on the features that matter most in your operations. For many reasons, trailer and 3-point sprayers are a smart investment: they allow you to utilize a tractor that would otherwise be sitting in your shed, offer tank sizes to fit your needs with small and large size options, and cause less compaction in your fields than self-propelled options.



#1 – Short Coupled Design

All FAST Sprayers are built to be as compact as possible. Our hitch pin to axle length is 3' to 4' shorter than some of our competition which gives your FAST sprayer a huge advantage when tracking on side slopes and headlands to minimize crop damage.




#2 – Industry Leading Boom Ride


With more resilient weeds in today's fields, even spray patterns and consistent boom ride is becoming increasingly important. FAST's field-proven, hydraulically-accumulated, center-pivot center section isolates the boom from the trailer and dampens any rough terrain. This provides level boom heights and excellent chemical coverage for superior weed kill.



#3 – Operator Friendly Plumbing

One example of FAST products being “Designed by Farmers, For Farmers” is the plumbing layout on all of our sprayers. It's easy to understand, and because the plumbing system is not covered it's easy to access. We use the products in our own fields and we know the importance of well laid out plumbing.





#4 – FAST “Stealth” Style Tank

US Patent #7,585,000. A low center of gravity and large trough sloped sump with excellent cleanout will keep the pump primed on long slopes. This tank also allows FAST to achieve its short coupled design along with multiple dual wheel options. Tanks sizes range from 1050-2400 gallons.



#5 – High Crop Clearance

All FAST sprayers are designed to maximize crop clearance with a single reach tongue and high axle heights, to allow for late season spraying with minimal crop damage. FAST is one of the industry's leaders in crop clearance design.



#6 – FAST Hydraulic AutoYaw Cushioning System

Unique to FAST and standard on all 120' and 132' sprayers, this ISO system will provide hydraulic cushioning when a boom moves forward or rearward caused by any type of sudden movement. This removes a significant amount of stress from the boom and results in a more durable, longer lasting design. This is a game-changer on our large boom sprayers.



#7 – High Quality/Resale Value

Built to last with heavy hinge areas and added laminate plates which hold up in the long run. Utilizes automated Powdercoat paint line and Magni coated hardware (1000 hour salt spray) to keep sprayer looking good years down the road. This keeps you running out in the field and a better resale value when it is time to trade.



#8 – Dual Wheel/Track Capability

Increase your flotation and decrease your compaction with many different dual options or CAMSO (formerly Camoplast) 15" track system. This also helps increase your application window and fits well with our 2400 gallon tank. Huge advantage compared to self-propelled sprayers and very important in pre-emerge spraying.



9600N/TF SERIES SPRAYER

This compact sprayer gives you the flexibility and performance you need. FAST has designed this boom to allow you to stay on your planter tracks and minimize traffic patterns on headlands and field borders. The 90' boom folds to spray at 60', the 80' boom folds to 40' and 60', and the 100' boom folds to 40' and 70'. The 60', 66', 88' and 90' booms are offered in a compact 10' center section (9600N). The 80' and 100' booms are offered in a 12' center section (9600TF).

Operators praise the compact design of the unit, which is desirable for field-tracking to minimize crop damage on hillside and when turning on headlands. This, along with FAST's field-proven, industry-leading boom ride and short-coupled trailer, has made this sprayer a favorite among operators.

FAST DESIGNED
BY FARMERS | FOR FARMERS





Short-Coupled Design

The 9600N/TF's short-coupled, high clearance trailer, with one of the shortest hitch-pin-to-axle lengths in the industry, provides superior tracking and minimized crop damage.



Industry-Leading Boom Ride

FAST's field-proven, hydraulically-accumulated, center-pivot center section isolates the boom from the trailer and dampens any rough terrain. This provides level boom heights and excellent chemical coverage for weed kill.



Boom Flexibility/ Decrease Traffic Patterns

Minimizing your footprint in the field and keeping consistent traffic patterns helps increase yield. Therefore, FAST has designed its 80' and 100' boom to fold and spray at 40' as well as a 90' boom that folds to spray at 60' to help stay on your planter tracks on end rows and field borders.

STANDARD FEATURES

- FAST "Stealth" Tank Design – U.S. Patent # 7,585,000, 1050 or 1350 gallon capacities offers a low center of gravity and a large troughed sloped sump with excellent cleanout which will keep the pump primed on long slopes
- Breakaway with Fore and Aft Movement - Increased durability and lighter weight with DOMEX® steel
- Adjustable Axle Position and Width - All FAST trailer sprayers have an adjustable axle receiver, movable from the middle position forward 9" to further improve tracking, or backward 9" to provide a more stable ride
- 100 Gallon Rinse Tank and Operator Friendly Fill Platform
- Ace Hydraulic 150-206F (60-66') or Ace Hydraulic 205-304F (80-100') pumps standard with an overspeed protection valve
- Powder Coat Paint - FAST's new automated five-stage wash and powder coat paint line provides a consistent process that gives our steel a durable, attractive finish
- Quality in the Details - FAST's commitment to quality shows up in the details. We improve the life of our product by using DOMs and greasable pins in highly corrosive areas, which leads to a longer-lasting, higher-quality product

KEY OPTIONAL FEATURES

- 380/90R46 Tires - Singles or Duals (also offered in 320/90R46 Duals), reduce soil compaction. Spacing options of 62-120", 80-120", and 88-132"
- Electronic Sight Gauge - Provides a more accurate measurement to allow more efficient chemical management (1350 gal tank only)
- Hypro Cleanload Eductor - Quick and easy way to mix chemical
- Electric Fenceline Nozzles – Increase the weed kill on field borders from the convenience of your cab



9500T SERIES SPRAYERS

The 9500T Series Sprayer gives operators the ability to cover more acres in a shorter amount of time with our truss-style 120' or 132' booms.

The round tube truss-style boom incorporates DOMEX® steel in higher stress areas to reduce weight and add strength. It is designed to increase boom life and allow operators to spray at higher speeds.

FAST's Hydraulic AutoYaw system gives the boom hydraulic cushioning on fore and aft movements to significantly reduce boom stress on sudden stops, starts, and turns.

This boom also has the flexibility to fold and spray at 90', with an option to spray at 60' or 66'.

The 9500T Series offers 1800 or 2400 gallon tank capacities with FAST's patented "Stealth" style tank, while still having one of the shortest hitch pin-to-axle lengths in the industry.

FAST DESIGNED
BY FARMERS | FOR FARMERS





FAST Hydraulic AutoYaw Cushioning System

Unique to FAST and standard on all 120' and 132' sprayers, this ISO system will provide hydraulic cushioning when a boom moves forward or rearward caused by any type of sudden movement. This removes a significant amount of stress from the boom and results in a more durable, longer lasting design. This is a game-changer on our large boom sprayers.



Electronic Sight Gauge (Optional)

Utilizes a float that is placed in the absolute center of the tank to give an accurate tank level measurement. Provides a more accurate measurement for efficient chemical management, and more accurate partial loads.



Raven Hawkeye Pulsing Nozzle System (Optional)

Utilizes a pulsing solenoid in each nozzle body to keep consistent pressure and droplet size through a given speed range (commonly 5-14 mph). Provides consistent spray coverage and can be used to minimize drift. Can be equipped on most FAST sprayers.

STANDARD FEATURES

- FAST "Stealth" Tank Design – U.S. Patent #7,585,000. 1800 or 2400 gallon capacities offer a low center of gravity and a large troughed sloped sump with excellent cleanout which will keep the pump primed on long slopes
- Industry-Leading Boom Ride – FAST's field-proven, hydraulically-accumulated, center-pivot center section isolates the boom from the trailer. This provides level boom heights and excellent chemical coverage for weed kill.
- Breakaway with Fore and Aft Movement – Increased durability and lighter weight with DOMEX® steel
- Adjustable Axle Position and Width – All FAST trailer sprayers have an adjustable axle receiver, movable from the middle position forward 9", to further improve tracking, or backward 9", to provide a more stable ride
- 3" Quick Fill, 100P Flow Meter, and 1-1/2" Motorized Control Valve
- Pump Hydraulic Flow Limiter – Provides over-speed protection
- Quality in the Details – We improve the life of our product by using DOMs and greasable pins in highly corrosive areas, which leads to a longer-lasting, higher-quality product

KEY OPTIONAL FEATURES

- Larger Single Tires or Duals - Multiple options to increase your flotation and reduce soil compaction, such as the 380/90R54 Duals with a 20k - 10 Bolt Hub. Spacing options of 62-120", 80-120", and 88-132"
- 15" CAMSO (Camoplast) Tracks - Increase your flotation and decrease your compaction. This also helps increase your application window and fits well with our 2400 gallon tank.



9500TF SERIES SPRAYER

The 9500TF Series Sprayer allows operators to spend more time spraying and less time filling with our 1800 or 2400 gallon tank, while still offering one of the shortest hitch pin-to-axle lengths in the industry in this tank size category.

The 9500TF is also designed to allow you to minimize traffic patterns in the field with a 80' boom that folds to 40' and 60', a 90' boom that folds to spray at 60', and a 100' boom that folds to 40' and 70'.

This model also offers boom sizes from 60'-100' with a boom ride that is second to none with FAST's hydraulically accumulated center pivot center section and industry leading durable boom design.



FAST DESIGNED
BY FARMERS | FOR FARMERS



STANDARD FEATURES

- FAST "Stealth" Tank Design – U.S. Patent #7,585,000, 1800 or 2400 gallon capacities offers a low center of gravity and a large troughed sloped sump with excellent cleanout which will keep the pump primed on long slopes
- Breakaway with Fore and Aft Movement
- Tri-Fold Boom Design – 90' boom will fold to 60' and 80' boom will fold to spray at 40'. 100' boom gives a very compact design with short hitch pin-to-axle length compared to other designs on the market.
- Adjustable Axle Position and Width – All FAST trailer sprayers have an adjustable axle receiver, movable from the middle position forward 9", to further improve tracking, or backward 9", to provide a more stable ride
- Dual Wheel Capability – 62-120", 80-120", 88-132"
- 100 Gallon Rinse Tank and Operator Friendly Fill Platform
- Ace Hydraulic 205-304F pump with hydraulic flow limiter to provide overspeed protection, adding longevity to your pump
- Powder Coat Paint – FAST's new automated five-stage wash and powder coat paint line provides a consistent process that gives our steel a durable, attractive finish

Industry-Leading Boom Ride



FAST's field-proven hydraulically-accumulated center-pivot center section isolates the boom from the trailer and dampens any rough terrain. This provides level boom heights and excellent chemical coverage for superior weed kill.

Operator Friendly Plumbing



The plumbing on all FAST Sprayers is simple to understand, and easy to access and operate. FAST understands the needs of today's farmers, and designs products to make the farmer more efficient and profitable.

2400 Gallon Tank & Tracks



Upgrade to a 2400 gallon tank and CAMSO 15" wide tracks to maximize flotation and cover more acres per day. The CAMSO tracks feature unmatched durability and flexibility while decreasing compaction by 78% compared to 380/90R46 Singles.

KEY OPTIONAL FEATURES

- Larger Single or Dual Tires – Multiple options to reduce soil compaction. Dual spacing options of 62-120", 80-120", and 88-132"
- Electronic Sight Gauge – Provides a more accurate measurement to allow more efficient chemical management
- CAMSO (Camoplast) 15" TTS tracks system – help minimize soil compaction and increase your application window



TRACK TANKS

FAST Inboard Track Tanks allow you to maximize the use of the equipment you have already invested in your operations.

973PT 3-POINT BOOMS

The 973PT utilizes our 120-132' truss-style boom, to increase boom life while decreasing overall weight.

FAST's Hydraulic AutoYaw system gives the boom hydraulic cushioning on fore and aft movements to significantly reduce boom stress on sudden stops, starts, and turns.


As can be expected from FAST, operators praise the industry-leading boom ride that is driven from our hydraulically accumulated center pivot center section. These booms will allow you to make the same pass through the field with half of the footprint and less opportunity for crop damage, which is extremely beneficial in areas with more hillsides or in smaller fields.

**FAST DESIGNED
BY FARMERS | FOR FARMERS**



Compact Design

These inboard tanks are mounted inside the track. This keeps the tanks from increasing the transport width of the tractor, giving the operator more flexibility and less liability during transport.



ISO Hydraulic Yaw Control

ISO electronically controlled hydraulic boom relief system designed to allow the boom wing fold-cylinder to flex and retract as needed. This dissipates the accelerations of the boom's wings (tractor must be ISO compatible). This system is unique to FAST equipment, and will cushion any abrupt movements to allow for a lighter, longer-lasting boom.

973PT STANDARD FEATURES

- The same FAST field-proven boom design that is used in the trailer sprayers
- Truss style boom utilizing high strength, lighter weight DOMEX® steel incorporated into the design to provide a strong structural boom with decreased overall weight
- Breakaway with Fore and Aft Movement – Increased durability and lighter weight with DOMEX® steel
- Ace 205-304F Hydraulic Pump with hydraulic flow limiter to provide overspeed protection
- Triple Nozzle Bodies
- Adjustable Wing Rest and Parking Stands
- Powder Coat Paint

KEY OPTIONAL FEATURES

- ISO Ready Connection
- Hypro Cleanload Chemical Educator
- Raven ISO Auto Boom Height Control
- Fenceline Nozzles



Case-IH Steiger Rowtrac Tanks

FAST also offers 1,000 gallon stainless steel tanks to fit on Steiger Rowtrac tractors. These tanks minimally increase transport width, mount to the outside of the track assembly, and follow the hood line of the tractor for visibility. Pair with a FAST 3-Point sprayer and/or FAST sidedress applicator to maximize equipment utilization and have great flotation.

TRACK TANKS

FAST Track Tanks are compatible with John Deere and Case-IH Steiger Rowtrac (1000 gallon capacity) as well as Challenger (850 gallons) track tractors and give you maximum flexibility to utilize in multiple applications, such as starter fertilizer, sidedressing, and spraying. These tanks are made out of stainless steel with increased life for high durability and excellent cleanout. Operators praise the smooth ride and flexibility obtained from these tractor mounted tanks.

TRACK TANK STANDARD FEATURES

- Excellent Weight Distribution - Optimum ride and maximum flotation
- Sparger Tubes – Full Length, Stainless Steel
- Made from 10 Gauge Stainless Steel
- Rinse Out System
- Stainless Steel Welded in Baffles
- Rubber Mounted on Frame
- External Sight Gauge
- Powder Coat Paint



953P SERIES SPRAYERS

The 953P helps minimize tracks in the field and provides a great alternative to a self-propelled sprayer at a fraction of the cost. FAST utilizes a single 500 or 750 gallon tank with FAST's field proven boom design from 60'-100'. This sprayer will be an excellent addition to your operation, especially in tighter fields and in hilly conditions.

This sprayer also works very well to spray field borders with minimal crop damage.



Easy Access Plumbing

Similar to all FAST sprayer designs, the 953P has all of its main plumbing controls on one side of the sprayer, is easy to access, and easy to understand.

Pair With FAST Track Tanks

Add another 850-1000 gallons without pulling a trailer by pairing this sprayer with Track Tanks while still achieving great flotation in the field.



One Main Tank

Other designs utilize two tanks rather than one. A single tank design provides for better/even cleanout of the tank and the ability to keep your pump primed more effectively on hillsides.

STANDARD FEATURES

- Tri-Fold Boom Design – 80' boom folds to spray at 40' and 90' boom folds to spray at 60' to help minimize traffic patterns while spraying fields borders and headlands
- Ace Hydraulic 150-206F (60-66') or Ace Hydraulic 205-304F (80-100') pumps standard with an overspeed protection valve
- Center Pivot Center Section – provides stable boom ride
- Breakaway with Fore and Aft Movement - Increased durability and lighter weight with DOMEX® steel
- Compact Transport Position – provides great visibility
- 50 Gallon Rinse Tank

963PTF SERIES SPRAYERS

FAST's 963PTF boom gives you great flexibility to work with both wheel or track tractors, and makes a great combination with our FAST Track Tanks. This 60'-100' boom with a hydraulically accumulated center industry-leading center section will give you superior boom ride and allow your operation to become more efficient and profitable.



Parallel Link System

All of FAST's three point mounted sprayers use the same parallel link system as our trailer sprayers. This gives you maximum boom height adjustability for all stages of crop growth.



ISO Ready Connection

All FAST Sprayers can be configured to run product control through your ISO ready tractor and in-cab display. This gives you the ability to utilize section control and minimize clutter in your cab.

STANDARD FEATURES

- Hydraulically Accumulated Center Pivot Center Section – Isolates boom from the tractor and provides a stable boom ride for superior weed kill
- Tri-Fold Boom Design – 80' boom folds to 40' and 60', 90' boom folds to spray at 60', and 100' boom also folds to 40' and 70' to help minimize traffic patterns while spraying fields borders and headlands
- Stainless Steel Wet Boom Plumbing – Higher flow rates, better chemical residual cleanout
- Ace Hydraulic 150-206F (60-66') or Ace Hydraulic 205-304F (80-100') pumps standard with an overspeed protection valve
- Parking Stands and Safety Light Kit



BIG WHEEL 500 & 750 SPRAYERS

These sprayers are an excellent addition to your operations in areas with more hillsides and compact fields, while still receiving the same high level of quality you expect from all FAST products.

Operators can choose from the 500 gallon tank with a 45' boom or a 750 gallon tank with a 60' boom.

As with all FAST sprayers, this trailer is also designed to minimize crop damage with its compact design and make it an operator-friendly sprayer to use.



Valve Tower

A handy valve tower allows the operator to know which valves to turn in an easy-to-operate manner.



Center Pivot Hydraulic Fold Boom

The BW500 and BW750 feature a hydraulic lift with parallel lift arms and a single-acting hydraulic cylinder. This, along with hydraulically-accumulated center section, give a stable boom ride and spray heights up to 51".

STANDARD FEATURES

BW500

- 45' Hydraulic Fold and Hydraulic Wing Tilt Boom
- 500 Gallon Tank
- 12.4 x 24" or 11.2 x 38" Tire Options

BW750

- 60' Hydraulic Fold and Hydraulic Wing Tilt Boom
- 750 Gallon Tank
- 13.6 x 38" Tires
- 50 Gallon Rinse Kit- In-line Filter Kit (3) for Boom feed lines
- 5 Gallon Chem Inductor

SHARED

- Short Coupled Design - Improve Tracking, less crop damage
- High Crop Clearance
- Adjustable Agitation Jets
- Ace 540 PTO pump or Ace 150-206F Hydraulic Pump

UT3P SPRAYERS

The FAST UT3P Sprayer is excellent for spraying in hard-to-reach areas or field corners. It is also ideal for rescue spraying and spraying along fence lines.

Manual Folding Boom sizes are 25', 30', and 40' along with Hydraulic Folding Boom Sizes of 40' and 45' with tank sizes of 250 or 300 gallons. A boomless option is also available for the UT3P sprayer, which utilizes two broadcast nozzles mounted on the back of the tank frame.



Narrow Transport Width

Hauling the FAST UT3P Sprayer down any road is not a problem, as it is designed with a 8' transport width.



Hydraulic or Manual Fold Boom

Choose the best fit for your operation. Manual fold booms come in 25', 30', or 40' options. Hydraulic folding booms utilize two tractor hydraulic outlets and are offered with 40' or 45' boom sizes. Both style booms utilize a breakaway boom the breaks both forward and rearward.



STANDARD FEATURES

- Extremely durable boom design features the same type of breakaway wings that are used in the larger FAST sprayers
- Hypro 6500C PTO 540 4 Roller Pump - standard on all UT3P sprayers
- FAST Pasture UT3P Tanks - Offered in either 250 or 300 gallon capacities.
- Ace Hydraulic 75-204 Pump - Optional
- Hypro Boom Extender Nozzles - Boomless Option
- Three Point Mount to Tractor - Category II and II
- Parking Stand and Fork Pockets integrated into the frame - stand on its own
- Safety Light Kit
- Hand Wand
- Powder Coat Paint



FAST AG SOLUTIONS SPRAYER SPECIFICATIONS

MODEL	9600N/TF (60'-100')	9500TF (60'-100')	9500T (120'-132')	953P	BIG WHEEL
Transport Height	10'7" (60') or 11'10" (90')	10'8" (60') or 11'11" (100')	13'3"	N/A (Tractor Dependent)	8'4" (BW500)
Transport Width	10'1" - 60', 66', 90' (N) 12'3" - 80', 100' (TF)	12'3"	12'4"	12'3"	8'1" (BW500)
Transport Length	18'5"	21'6"	23'10"	12'9"	17'6" (BW500)
Transport Weight Empty	7,620 (9613N 90')	8,300 (9518TF 90')	11,860 (9518T 120')	5,620 (90')	3,240 (BW500)
Field Weight Tanks Full	19,780 (9613N 90')	24,090 (9518TF 90')	27,200 (9518T 120')	9,620 (500 Gal 90') 11,880 (750 Gal 90')	8,320 (BW500)
Tank Size Gallons	1050 or 1350	1800 or 2400	1800 or 2400	500 or 750	500 or 750
Boom Sizes	60', 66', 80', 88', 90', 100'	60', 66', 80', 88', 90', 100'	120' or 132'	60', 66', 80', 88', 90', 100'	45' or 60'
Tank Rinse System	100 Gallon Rinse Tank	100 Gallon Rinse Tank	100 Gallon Rinse Tank	50 Gallon Rinse Tank	50 Gallon Rinse Tank
Standard Pump	Ace 150-206F (60', 66') or Ace 205-304F (80' - 100')	Ace 205-304F	Ace 205-304F	Ace 150-206F (60', 66') or Ace 205-304F (80'-100')	Ace 540 PTO
Standard Tires	13.6x38" or 320/90R46	380/90R46 or 480/80R50	380/90R46 or 480/80R50	N/A	12.4x24" or 11.2x38" (BW500) 13.6x38" (BW750)
Dual Wheel Capability	Yes: 60"-120", 80"-120", 88"-132"	Yes: 62"-120", 80"-120", 88"-132"	Yes: 62"-120", 80"-120", 88"-132"	N/A	No
Quick Fill	2"	3"	3"	2"	2"
Hitch-pin-to-axle Length	152"	175"	175"	N/A	144" (BW500)

WINDOM, MN

4130 Commerce Blvd, Windom, MN 56101
toll free 800.772.9279 • p 507.427.3861 • f 507.427.3030

GILMAN, IL

1340 S Crescent, PO Box 236, Gilman, IL 60938
toll free 800.872.8894 • p 815.265.7125 • f 815.265.7130